



AMDOR Roll-Up Compartment Door Specification

Compartment doors shall be equipped with AMDOR brand roll-up doors complete with the following features:

- 1" aluminum double wall slats with continuous ball & socket hinge joint designed to prevent water ingress and weather tight recessed dual durometer seals
- Double wall reinforced bottom panel with stainless steel lift bar latching system
- Bottom panel flange with cut-outs for ease of access with gloved hands
- Reusable slat shoes with positive snap-lock securement
- Smooth interior door curtain to prevent equipment hang-ups
- One-piece aluminum door track / side frame
- Top gutter with non-marring seal
- Non-marring recessed side seals with UV stabilizers to prevent warping
- Dual leg bottom seal (wear component material to be Type 6 Nylon)
- Door ajar switch system shall be provided by AMDOR. Magnetic, mechanical, and remote operated options are available.
- Door striker will provide support beneath the lift bar to prevent door curtain bounce and potential false door ajar indications.
- Optional wet paint shall be applied by AMDOR using a 4 stage base clear-coat system applied over an anodized substrate material for corrosion protection.

No exceptions or substitutions to this AMDOR Roll-Up Door specification are acceptable.

**If you have any questions or would like additional information please call your local AMDOR representative or our customer service team at
1-877-462-6367 / info@amdor.com**